



multiV+ 150					
Breite: 186 mm					
Nennweite: 150 mm					
Länge: 1000 mm					
Kanal-name	Höhe (mm)		Hydraulik-querschnitt	Ø Ausgang	
	a	b		Vert.	Horiz.
R150G00R	170	128	156	160	-
R150G10R	220	178	218	160	-
R150G20R	270	228	283	160	-
R150G30R	320	238	350	160	-



IBL Baustoff+Labor GmbH

Theillissengasse 3

A-2201 Gerasdorf bei Wien

Tel: +43(0)2246 - 20 500

Fax: +43(0)2246 - 20 500 / 20

ibl@ibl.at www.ibl.at

Description

ULMA polymer concrete linear drainage channel model multiV+ 150G. Self-cleaning optimized V-shaped V+ section. Protective galvanized steel edge with a real thickness of 2x2 mm, smooth, without breakage of the protective zinc layer, avoiding water accumulation and preventing corrosion. Boltless locking system ULMA Rapidlock®, 8 fixing points per lm for higher mechanical stability. Load class up to D400, EN 1433 Standard. CE Conformity Declaration and compliance with EN 1433 Standard. External width 186 mm, internal width 150mm and total length 1000mm. Total external heights available between 170mm and 320mm. Installation possible with no slope or stepped fall.